

CAT5E DATA JACK

90° DEGREE STYLE (SHIELDED)


Jack2Rack

DESCRIPTION

Category 5E Shielded Data Grade Keystone Jack 90° Degree 8x8 Conductors.

FEATURES

- 360° Shielding Structure to prevent EMI
- 110-IDC Contacts (Terminal Block)
- Color Coded for 568A and 568B
- EIA/TIA 568A/B standards
- ANSI/TIA-568-C.2 , ISO/IEC11801, EN50173-1
- Thermoplastic ABS Housing
- RoHS Compliant



SKU: 301-J2630/S

Physical Specifications

Dimension (mm) 19.35H x 21W x 46.83D

Housing Material

Housing & Cap Polycarbonate

Contact Material

IDC 110 Contacts 100µ Inch nickel plated over phosphor bronze
IDC Operating Life Minimum 250 re-terminations
Jack Contact Phosphor bronze, 50µ inch gold plating over nickel
Jack Operating Life Minimum 750 insertions
Compatibility 23 to 26 AWG (solid)

Shielded Cover


50~60µ inch nickel plated over phosphor bronze

Product Qualifications

ANSI/TIA-568-C.2
ETL Listed

Electrical:

Dielectric strength 1000V RMS for 1min
Insulation resistance 10mΩ min
Contact Resistance 2mΩ per contact
Temperature Range -10°C to 60°C max
Humidity 10%~65%



Jack2Rack

Tel: 951 696-5481

Tel: 951 696-5478

Email: sales@jack2rack.com



www.jack2rack.com

Rev. 06/2011